



REF-LOCATOR

Item Number 4686714

Leak detector based on heated solid electrolyte sensor technology. The sensor has an above-average lifetime of approx. 10 years. The REF-LOCATOR is supplied in a practical, sturdy plastic case.

- Very high sensitivity of 1.4 g/year
- Fast localization thanks to three easily adjustable sensitivity levels
- With 3 UV and 3 LED inspection lights
- No UV-glasses required

Technical Data

Material	ABS TPU
Colour	yellow (RAL 1023) green (RAL 6026)
Standards	SAE-J2791, SAE-J2913, EN14624:2012, ASHRAE Standard 173
RoHS Conformity	1
RoHS Conformity	Yes
Temperature Range	-4 - 52 °C
Ingression Protection	IP54
Battery	4 x AA
Operating Hours	4 h
Functions	3-level sensitivity, Ambient concentration reset, Mute function, Low battery indication, UV-light and LED,

Auto power off

Sensitivity	1.4 g/a (0.05 oz/yr) all HFC's incl. R410A, R404A, R407C ,R134a, R32 0.7 g/a (0.025 oz/yr) for HCFC R22 0.9 g/a (0.03 oz/yr) for HFO R-1234yf
Refrigerant Type	CFC HCFC HCF HFO Refrigerants
Measurement Technology	Electrical
Sensor Lifetime	10 y
Tube Length	43 cm
Scope of Supply	Batteries Instruction manual Spare Filter
Packaging	Sturdy plastic case
Warm-up Time	30 s

Accessories

4492022	TL-5	Reference leak for leak detectors, 5g / year
---------	------	--

Spare Parts

4686822	REF-LOCATOR-SEN-01	Replacement sensor for REF-LOCATOR
4686821	LOCATOR-FILTER/5	Spare filter, 5 pieces
4686705	REF-LOCATOR-TV-01	Test vial for REF-LOCATOR
4687034	LOCATOR-LED-UV/6	Spare LED UV for leak detector, 6 pcs.
4686828	LOCATOR-LED-WHITE/6	spare LED white for leak detector, 6 pcs.
4686707	REF-LOCATOR-CASE	Case for leak detector