



REF-METER-OCTA-KIT

Item Number 4681989

Combi set containing REF-METER-OCTA and REF-METER-OCTA-PLUS

- High accuracy from +/- 0.5 %, up to 110 kg
- Field calibration possible
- Programmable alarm for defined level
- Fill level determination in kg or %
- All common weight units available
- Control box and cable integrated in the housing
- With screw-in thread for 10612-REF for mounting refrigerant cans
- Power supply via 4 AAA batteries, 30 hours battery life
- Reliable filling of refrigeration system
- Prevents overfilling of refrigerant cylinders

Technical Data

Material	Steel Aluminium Brass ABS
Colour	yellow (RAL 1023) green (RAL 6026) black
Standards	EN 62479: 2010 EN 60950-1:2006+A11:2009+A1:2010+A12:2011+A2:2013 EN 61326-1:2013 EN 55022: 2006 + A1: 2007 EN 55024: 1998 + A1: 2001 + A2: 2003
RoHS Conformity	1
RoHS Conformity	Yes
Connector A	1/4" SAE Outside thread
Connector B	1/4" SAE Outside thread
Working Pressure	34 bar

Temperature Range	10 - 40 °C
Measuring Range	0 - 110 kg
Units	kg, lbs & oz
Resolution	2 g, 0.005 lbs, 0.1 oz
Battery	4 x AAA 4 x AA
Operating Hours	30 h
Functions	Hold mode (for bottle change), Programmable alarm, Tank capacity mode, Calibration, Battery level, Over-range indication, Switches the valve of REF-METER-OCTA-PLUS with optical interface, Thread to mount 10612-REF
Cable Length	150 cm
Scope of Supply	Control box Batteries Pouch Instruction manual
Packaging	Cardboard box
Accuracy	+/- 0.5%

Accessories

4677027	10612-REF	Charging adapter for REFCO scales for refrigerant cans
4682773	10612-REF-1/4"SAE	Support device for liquid filling and charging of refrigeration cans

Spare Parts

4679462	REF-METER-OCTA	Electronic charging scale, capacity: 110 kg Accuracy: +/- 0.5%, Resolution: 2 g
4681823	REF-METER-OCTA-PLUS	Solenoid valve for OCTA scales
4686813	REF-METER-	Replacement control box for REF-METER-OCTA

Acknowledged globally



OCTA-CB

4686846

REF-METER-
OCTA-CP

Carrying pouch for REF-METER-OCTA